

## LIGHTWEIGHT ANTI-BALLISTIC SHIELDS

<b>Product application</b>	Tactical anti-ballistic shield
<b>Type of protective cover</b>	Black textile or Rosist®
<b>Composition</b>	<ul style="list-style-type: none"> <li>Al<sub>2</sub>O<sub>3</sub> ceramic</li> <li>Aramid backing</li> </ul>
<b>Dimensions</b>	<ul style="list-style-type: none"> <li>Lower shield: 500 x 1000 mm ± 5 mm</li> <li>Upper shield: 500 x 1000 mm ± 5 mm</li> </ul>
<b>Weight</b>	<ul style="list-style-type: none"> <li>Trolley: 54 kg ± 3 kg</li> <li>Lower shield: 32 kg ± 2 kg</li> <li>Upper shield: 39 kg ± 2 kg</li> </ul>
<b>Shape</b>	<ul style="list-style-type: none"> <li>Rectangular, flat</li> </ul>
<b>Main characteristics</b>	<ul style="list-style-type: none"> <li>Composed of 2 ballistic shields &amp; 1 chassis</li> <li>Assembly/disassembly of the complete shield on chassis is tool-less</li> <li>Adjustable height from 1650 mm to 1950 mm</li> <li>Chassis with 4 rotating wheels 360°</li> <li>Brake on the rear wheels</li> <li>Additional ballistic plate NIJ III + MSC to protect feet (during standby phase)</li> </ul>
<b>Created</b>	September 1, 2023

## AVAILABLE ACCESSORIES

<ul style="list-style-type: none"> <li>Camera (D/N; thermal)</li> </ul>	<ul style="list-style-type: none"> <li>Lamp (LED, IR, laser)</li> </ul>
Details on request	

## SPECIAL THREATS TESTED

Test temperature of 20°C
Multi hit (100 mm between shots)
<ul style="list-style-type: none"> <li>NIJ 0108.01, Niveau IV: .30-06 APM2</li> <li>7.62 x 54 R API B32 (854 m/s ± 10 m/s)</li> <li>7.62 x 39 API BZ (730 m/s ± 10 m/s)</li> <li>NIJ 0108.01, Level III: 7.62 x 51 M80</li> </ul>
The above list of ammunition is not exhaustive and may not include threats that can be defeated by this product.



## GUARANTEE PERIOD

The shield is expected to preserve its conformity with the specifications for a period of at least 5 years during storage from the date of delivery, provided that:
<ul style="list-style-type: none"> <li>The product is stored under dry conditions at normal ambient temperature</li> <li>The product is stored vertically</li> <li>The product has not been subjected to peak temperature exceeding 70°C</li> <li>The product is protected against long term direct exposure to sun light</li> </ul>

## HANDLING

<ul style="list-style-type: none"> <li>Keep away from intense heat source</li> <li>Do not drop the shield on the floor and avoid hard shocks</li> <li>Do a visual inspection of the shield every six months</li> <li>In case of visual damage, send the shield back for inspection/repair</li> <li>Only clean with pure water and mild soap</li> <li>Use only as a shield, do not sit or walk on it</li> </ul>
--

# CS-800 TL / K-OPS 500



Although Integris has used diligent care to ensure that the information provided in this document is accurate and up to date, Integris makes no representation or warranty, express or implied, as to the accuracy, reliability or completeness of the information. In no event shall Integris be liable for any damages arising from the reader's reliance upon, or use of, the information or materials contained in this document. The reader shall be solely responsible for any interpretation or use of this information and materials. The content of this document is subject to change without further notice. Please contact your Integris representative for more details.



# INTEGRIS