































SERIES		SPECIAL THREATS TESTED		PROTECTION LEVEL	SPECIFICATIONS				STAND ALONE	THICKNESS *1	WEIGHT *2
950 In Conjunction with VPAM 3 vest	CX	 7.62 X 37 SWISS	<ul style="list-style-type: none"> •7.62 x 51 SWISS P AP •7.62 x 54 R API-B32 •7.62 x 51 AP P80 •7.62 x 39 AK47 API-BZ •5.56 x 45 SS109 	VPAM 12	 Multi-hit	 Ceramic / composite	 Multicurve / SAPI	 Stop in plate		30 mm	4,05 kg
850 In Conjunction with VPAM 3 vest	CX	 7.62 X 63 M2AP	<ul style="list-style-type: none"> •7.62 x 54 R API-B32 •7.62 x 51 AP P80 •7.62 x 39 AK47 API-BZ •5.56 x 45 SS109 •7.62 x 51 DM111 	VPAM 10	 Multi-hit	 Ceramic / composite	 Multicurve / SAPI	 Stop in plate	✓	26 mm	2,75 kg
750 In Conjunction with VPAM 3 vest	CX	 7.62 X 51 AP P80	<ul style="list-style-type: none"> •7.62 x 51 AP P80 •7.62 x 39 AK47 API-BZ •5.56 x 45 SS109 •7.62 x 51 DM111 •7.62 x 39 AK 47 MSC 	VPAM 9	 Multi-hit	 Ceramic / composite	 Multicurve / SAPI	 Stop in plate	✓	20 mm	2,40 kg
	CS									18 mm	3,05 kg
650 In Conjunction with VPAM 3 vest	CX	 7.62 X 39 API BZ	<ul style="list-style-type: none"> •7.62 x 39 AK47 API-BZ •5.56 x 45 SS109 •7.62 x 51 DM 111 •7.62 x 39 AK 47 MSC 	VPAM 8	 Multi-hit	 Ceramic / composite	 Multicurve / SAPI	 Stop in plate	✓	16 mm	2,15 kg
550 Stand Alone	CS	 5.56 X 45 SS109	<ul style="list-style-type: none"> •7.62 x 39 MSC •7.62 x 51 DM111 •5.56 x 45 SS109 	VPAM 7	 Multi-hit	 Ceramic / composite	 Multicurve / SAPI	 Stop in plate		26 mm	2,20 kg
450 In Conjunction with VPAM 3 vest	CXP	 7.62 X 39 MSC	•7.62 x 39 AK 47 MSC	VPAM 6	 Multi-hit	 Fully composite	 Multicurve / SAPI	 Stop in plate	✓	12 mm	0,80 kg
	CX									23 mm	1,55 kg

*1 Tolerances: +/- 2mm | *2 Tolerances: +/- 0,5 Kg